


**Specification:** T&C Plastics SS-\_\_\_\_\_ gravity oil interceptor with \_\_\_\_\_ U.S. gallons of liquid holding capacity has a limited lifetime warranty and is made in the U.S.A. out of seamless, rotationally molded High Density Polyethylene with 3/8" uniform wall thickness. Interceptor is designed for above or below ground installation and includes an adjustable lid system, sample port access, deep seal trap covered by lid, internal air relief by-pass, adjustable oil draw-off assembly (1 1/2" I.P.S.) on each side, double vent connections (3" I.P.S.) on each side, stainless steel calibrated orifice plate (internal flow control), base for support and floor level installation and 4" no hub inlet and outlet connections. Steel encased composite lids provide a water / gas tight seal and have a minimum of 20,000 LB. load capacity - in accordance with the loading requirements of AASHTO H20. The high density polyethylene material is PE 3135 from Dow 9.39 with a density of 0.939 g/cm3. For indoor/outdoor use.

**Function:** Oil interceptors are required anywhere oil and sand may be introduced to the public sewer system in applications such as: repair garages, oil change stations, car wash facilities, parking garages, parking lots, hydraulic elevator pits and facilities where oil and flammable liquid waste are produced as a result of manufacturing, storage, maintenance, repair or testing processes. The interceptor collects the oil before it is drained to an adjacent storage tank through an adjustable draw off system. Typically installed either on or into the floor. Regular maintenance is required to keep the interceptor functioning. All T&C gravity interceptors can withstand a temperature of up to and including 180 degrees Fahrenheit.



Model	Flow Rate (GPM)	Liquid Cap. (Gal/cu.ft.)	Oil Storage Holding Capacity (Gallons)	Sand Capacity (Gallons)	A	B Width	C1 Dim.	C2 Dim.	D1 Dim.	D2 Dim.	E1 Dim.	E2 Dim.	F Connection Size	Shipping Weight (lbs.)
OI-SS-500	250	539 / 72	310	102	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	26.25" 667mm	24.25" 616mm	45" 1143mm	61.50" 1562mm	4" 102mm	960
OI-SS-750	250	772 / 103	413	316	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	34.88" 886mm	32.88" 835mm	53.63" 1362mm	70.13" 1781mm	4" 102mm	1,025
OI-SS-1000	250	1015 / 135	458	352	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	45.25" 1149mm	43.25" 1099mm	64" 1626mm	80.50" 2045mm	4" 102mm	1,085
OI-SS-1250	250	1262 / 168	569	438	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	56.25" 1429mm	54.25" 1378mm	75" 1905mm	91.50" 2324mm	4" 102mm	1,160
OI-SS-1300	250	1312 / 175	592	455	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	56.25" 1429mm	54.25" 1378mm	75" 1905mm	91.50" 2324mm	4" 102mm	1,160
OI-SS-1500	250	1522 / 202	624	493	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	64" 1626mm	62" 1575mm	82.75" 2102mm	99.25" 2521mm	4" 102mm	1,260
OI-SS-2000	250	2022 / 269	829	655	111" 2820mm	64" 1630mm	18.75" 476mm	37.25" 946mm	85.50" 2172mm	83.50" 2121mm	104.25" 2648mm	120" 3048mm	4" 102mm	1,350

Suffix	Optional Variations	Suffix	Optional Variations
-AK	Anchor Kit for all SS Units	-POK	Remote Pump Out Kit
-C	Lid Extension (specify dimension required)	-RHSL	4" no hub inlet on right hand side
-COA	Coalescer Pack	-RHSL	4" no hub outlet on right hand side
-DI	Ductile Iron lid & collar	-RPO	4" Remote pump outlet connections on top of interceptor - specify location and number required
-FL-C	Membrane clamp kit	-SB	Sediment Bucket
-F6	6" No Hub Inlet / Outlet connection (flow rate of 700 GPM with 6" connection)	-SP	External sampling port - inline, high connections
-F8	8" No Hub Inlet / Outlet connection (fabricated stainless steel) (flow rate of 1,200 GPM with 8" connections)	-SP-L	External sampling port - inline, low connections
-HLA	High level alarm and float switch (to be installed on site)	-SP-OF	External sampling port - offset
-HT	Holding Tank	-SST	Fire resistant fabricated stainless steel interceptor
-LHSL	4" no hub inlet on left hand side	-ST	Fire resistant fabricated 10 gauge powder epoxy coated steel interceptor
-LHSL	4" no hub outlet on left hand side	-V	Vent connection - 4" (specify number required and location - side and / or top)

UNLESS STATED OTHERWISE DIMENSIONS ARE IN INCHES	MATERIAL:	HDPE			TITLE:	SS Series Gravity Oil Interceptor	SERIES:	SS SERIES	REV:	 WWW.TANDCPLASTICS.COM 732-780-5300
	WEIGHT [lb]:		NAME	DATE			SHEET 1 OF 1	SIZE:		
	DO NOT SCALE DRAWING	CHECKED	DRAWN	DR			11/15/2022	SCALE: 1:2		

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TOWN & COUNTRY PLASTICS LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TOWN & COUNTRY PLASTICS LLC IS PROHIBITED.